

BIRCH, STEWART, KOLASCH & BIRCH, LLP

INTELLECTUAL PROPERTY LAW
8110 GATEHOUSE ROAD
SUITE 500 EAST
FALLS CHURCH, VA 22042-1210
USA

(703) 205-8000

FAX: (703) 205-8050
(703) 698-8590 (G IV)

e-mail: mailroom@bskb.com
web: http://www.bskb.com

CALIFORNIA OFFICE
COSTA MESA, CALIFORNIA

THOMAS S. AUCHTERLONI
JAMES T. ELLER, JR.
SCOTT L. LOWE
MARK J. NUEL, PH.D.
D. RICHARD ANDERSON
PAUL C. LEWIS
MARK W. MILSTEAD*
JOHN CAMPA*
RICHARD J. GALLAGHER

REG. PATENT AGENTS:
FREDERICK R. HANDREN
MARYANNE ARMSTRONG, PH.D.
MAKI HATSUMI
MIKE S. RYU
CRAIG A. McROBBIE
GARTH M. DAHLEN, PH.D.
LAURA C. LUTZ
ROBERT E. GOOZNER, PH.D.
HYUNG N. SOHN
MATTHEW J. LATTIG
ALAN PEDERSEN-GILES
JUSTIN D. KARJALA
C. KEITH MONTGOMERY
TIMOTHY R. WYCKOFF
HERMES M. SOYEZ, PH.D.
KRISTI L. RUPERT, PH.D.

HERBELL C. BIRCH
RAYMOND C. STEWART
JOSEPH A. KOLASCH
JAMES M. SLATTERY
BERNARD L. SWEENEY*
MICHAEL K. MUTTER
CHARLES GORENSTEIN
RALPH M. MURPHY, JR.
LEONARD R. SVENSSON
TERRY L. CLARK
ANDREW D. MEIKLE
MARC S. WEINER
JOE MCKINNEY MUNCY
ROBERT J. KENNEY
DONALD J. DALEY
JOHN W. BAILEY
JOHN A. CASTELLANO, III
GARY D. YACURA

OF COUNSEL:
HERBERT M. BIRCH (1905-1996)
ELLIOT A. GOLDBERG*
WILLIAM L. GATES*
EDWARD H. VALANCE
RUPERT J. BRADY (RET.)*
F. PRINCE BUTLER
FRED S. WHISENHUNT

*ADMITTED TO A BAR OTHER THAN VA.

Date: September 15, 2000
Docket No.: 2950-0172P

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): ROH, Jin Tae

For: METHOD AND APPARATUS FOR DETERMINING A RECORDABLE POSITION
OF A WRITABLE DISK

Enclosed are:

- ☒ A specification consisting of 17 pages
- ☒ 10 sheet(s) of Formal drawings
- ☐ An assignment of the invention
- ☒ Certified copy of Priority Document(s)
- ☒ Executed Declaration ☒ Original ☐ Photocopy
- ☐ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- ☐ Preliminary Amendment
- ☐ Information Disclosure Statement, PTO-1449 and reference(s)

The filing fee has been calculated as shown below:

SMALL ENTITY

FOR	NO. FILED	NO. EXTRA	RATE	FEE		RATE	FEE
BASIC FEE	***** ***** *****	***** ***** *****	***** ***** *****	\$690.00	or	**** **** ****	\$345.00
TOTAL CLAIMS	17 - 20 =	0	x18 = \$	0.00	or	x 9 = \$	0.00
INDEPENDENT	3 - 3 =	0	x78 = \$	0.00	or	x 39 = \$	0.00
MULTIPLE DEPENDENT CLAIM PRESENTED <u>no</u>			+260 = \$	0.00	or	+130 = \$	0.00

TOTAL \$ 0.00

No fee is enclosed.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. 1.16 or under 37 C.F.R. 1.17; particularly, extension of time fees.

BIRCH, STEWART, KOLASCH & BIRCH, LLP

JOSEPH A. KOLASCH

FB Reg. No. 22,463

P. O. Box 747

Falls Church, Virginia 22040-0747

005150 80829360

METHOD AND APPARATUS FOR DETERMINING A RECORDABLE POSITION OF A WRITABLE DISK

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to method and apparatus for recording new data in a writable disk after a previous recording to the disk is interrupted abnormally.

2. Description of the Related Art

FIG.1 is a simplified block diagram of a conventional
10 optical disk device for recording and reproducing data to/from a writable disk such as an once-recordable disk CD-R and a rewritable disk CD-RW. The disk device of FIG.1 comprises a digital recording signal processor 4b for converting input data into recording-formatted data as adding additional data such
15 as error correction codes, a channel bit encoder 11 for converting the recording-formatted data into EFM-formatted bit stream, a writing driver 12 for yielding a writing current according to an input bit stream, an optical pickup 2 for recording signals corresponding to the writing current onto an
20 optical disk 1 and reproducing recorded signals from the optical

disk 1, an R/F unit 3 for yielding servo error signals TE and FE, and binary signals through combining the reproduced signals from the disk 1, a digital reproducing signal processor 4a for restoring original data from the binary signals, a sled motor 5 9 for moving the pickup 2 radially, a spindle motor 10 for rotating the disk 1, a driving unit 8 for driving the motors 9 and 10, a servo unit 5 for controlling the driving unit 8 and the pickup 2 based on the servo error signals TE and FE, a microcomputer 6 for controlling overall operation of the servo 10 unit 5, digital signal processors 4a and 4b, and the writing driver 12 in order to record and reproduce data, and a memory 7 for storing data for the microcomputer 6 to use for supervising operation.

FIGS. 2 and 3 depict recording area format and an example 15 of recorded data for an once-recordable disk CD-R or a rewritable disk CD-RW. The writable disk is partitioned, as shown in FIG.2, into a power calibration area (PCA), a program memory area (PMA), and one or more sessions, each consisting of a lead-in area, a program area, and a lead-out area.

20 The PCA is used for writing data experimentally to determine an optimal writing power, and the PMA is reserved for recording information such as position and size of each recorded track which is data group recorded continuously without stop. Each track recorded in the program area is separated by a pause 25 section which is corresponding to about 2 second reproduction time.

The lead-in area has information on next recording position, that is, lead-in area position of neighboring next session. Therefore, when data recording is requested, a final 30 recording position, that is, next recordable position is detected easily and quickly through reading the lead-in area of a last session which was closed before.

FIG. 4 is a flow chart of writing new data adjacently to

previously-recorded data. The conventional data writing method of FIG. 4 to be conducted by the disk device of FIG. 1 is described.

When a user requests new data to be recorded in an inserted disk 1, the microcomputer 6 sets its mode to recording mode (S10), conducts an optimal power calibration (OPC) as recording and reproducing test data to/from the PCA, and sets an optimal writing power determined through the OPC into the writing driver 12 (S11).

After that, the microcomputer 6 reads position and size information, which is recorded in the PMA, about recorded tracks (S12), and searches for the first lead-in area, the second, and the third, in turn based on the PMA information (S13). For example, supposed that tracks 1 and 2 belong to the first closed session, tracks 3 and 4 belong to the second closed session, and tracks 5 and 6 are recorded next to the second closed session as shown in FIG. 5, the microcomputer 6 reads out position information of the second lead-in area 'LIA2' from the first lead-in area 'LIA1', and knows the next recording position, that is, the position of track 5 from the second lead-in area 'LIA2'.

Since the program area containing the tracks 5 and 6 is not closed into a session (S14), the microcomputer 6 examines the PMA information to know how many tracks are recorded in the disk 1 (S15), and locates final recorded track 6 based on the PMA information (S16). Then, the microcomputer 6 controls the digital recording signal processor 4b and the servo unit 5 to record new data separated a pause section off from the track 6. If all of the new data are recorded, the microcomputer 6 designates just-recorded data block as track 7, creates information on the recorded position and size about the track 7 and writes it in the PMA (S17).

Some time later, if the tracks 5 to 7 are requested to be closed in a session (S18), the microcomputer 6 groups the

0962303 091500 005160 8022360
tracks 5 to 7 into the third session, writes necessary information in the secured third lead-in area 'LIA3', and secures the third lead-out area 'LOA3' next to the last track (S19). After that, the above-explained recording operation will be conducted or not according to a user's request.

However, during the recording operation, a servo control may be failed due to a mechanical shock or a data buffer may be underruned, which causes the current recording operation to stop abruptly without writing track information or lead-in information. Therefore, the PMA information may represent real-recorded tracks wrongly or the lead-in area may contain invalid information.

For a writable disk suffered such a recording fail, it is impossible to detect last recording position exactly, so that new data may be overwritten onto previous data or unwritten area may arise between last recorded track and new recorded track. If previous data was overwritten by the new data, the previous data would be lost.

Especially, if the writable disk is once-writable one, the new recorded data as well as the previous data are damaged together when the previous data are overwritten since the surface is burned while recording and it can not be restored to unburned state.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method and an apparatus for determining a recordable position of a writable disk such as an once-recordable disk and a rewritable disk, which detects a recordable position from recording information, and verifies the detected recordable position to know whether it is the last position of actually-recorded data or not by examining recorded state changed from written data.

0366303-091500

A method of determining a recordable position of a writable disk according to the present invention, reads data recording information of the writable disk, examines whether an area after a recordable position indicated by the read data recording information has recorded data or not, and changes the recordable position to other position for new input data based on the examination result.

Another method of determining a recordable position of a writable disk according to the present invention, checks whether a previous recording has been done normally, examines a recording area affected by a writing beam during the previous recording according to the checked result, and determines a recordable position for new input data based on the examination result.

15 A disk recording/reproducing apparatus to which the above method according to the present invention is applied, comprising a pickup of writing input data and reading the written data to/from a writable disk; a moving means of moving the pickup across the writable disk; and a controller of
20 controlling the moving means to move the pickup, when recording of new data is requested, to a recordable position indicated by data recording information which was updated after previous data recording, checking whether or not recorded data exists after the indicated recordable position through examining the
25 state of a recording surface of the writable disk, and changing the recordable position for the new data to other position based on the checked result.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention, illustrate the preferred embodiments of the invention, and together with the description, serve to explain the principles of the present

invention.

In the drawings:

FIG.1 is a simplified block diagram of a conventional optical disk device for recording and reproducing data to/from a writable disk;

FIGS. 2 and 3 depict recording area format and an example of recorded data for an once-recordable disk CD-R or a rewritable disk CD-RW;

FIG. 4 is a flow chart of writing new data adjacently to previously-recorded data;

FIG. 5 describes an example of recorded data of a writable disk and a recording procedure to the disk;

FIG. 6 is a block diagram of an optical disk device to which a recordable position determining method according to the present invention is applied;

FIG. 7 is a flow chart of determining a recordable position of a writable disk according to the present invention;

FIG. 8 describes an example of recorded data and a recording procedure according to the present invention;

FIG. 9 describes another example of recorded data and a recording procedure according to the present invention;

FIG. 10 describes another example of recorded data and a recording procedure according to the present invention; and

FIG. 11 describes another example of recorded data and a recording procedure according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In order that the invention may be fully understood, preferred embodiments thereof will now be described with reference to the accompanying drawings.

FIG. 6 is a block diagram of an optical disk device to which a recordable position determining method according to the present invention is applied. The disk device of FIG.6 comprises

a digital recording signal processor 34b for converting input data into recording-formatted data as adding additional data such as error correction codes, a channel bit encoder 41 for converting the recording-formatted data into EFM-formatted bit stream, a writing driver 42 for yielding a writing current according to an input bit stream, an optical pickup 32 for recording signals corresponding to the writing current onto an optical disk 1 and reproducing recorded signals from the optical disk 1, an R/F unit 33 for yielding servo error signals TE and FE, and binary signals through combining the reproduced signals from the disk 1, a digital reproducing signal processor 34a for restoring original data from the binary signals, a sled motor 39 for moving the pickup 32 radially, a spindle motor 40 for rotating the disk 1, a driving unit 38 for driving the motors 39 and 40, a servo unit 35 for controlling the driving unit 38 and the pickup 32 based on the servo error signals TE and FE, a microcomputer 36 for controlling overall operation of the servo unit 35 and digital signal processors 34a and 34b, and the writing driver 42 in order to record and reproduce data, and checking the reproduced EFM-formatted binary signal from the R/F unit 33 to know whether a corresponding area has recorded data or not, and a memory 37 for storing data for the microcomputer 36 to use for supervising operation.

FIG. 7 is a flow chart of determining an actual recordable position of a writable disk according to the present invention. The method of FIG. 7 embodying the present invention to be conducted by the disk device of FIG. 6 is described in detail.

When a user requests new data to be recorded in an inserted disk 1, the microcomputer 36 sets its mode to recording mode (S30), conducts an optimal power calibration (OPC), and sets an optimal writing power determined through the OPC into the writing driver 32 (S31).

After the OPC, the microcomputer 36 reads position and

size information, which is recorded in the PMA, about recorded tracks (S32), and searches for the first lead-in area, the second, and the third, in turn based on the PMA information and chained information between lead-in areas (S33).

5 For example, supposed that tracks 1 and 2 belong to the first closed session, tracks 3 and 4 belong to the second closed session, and tracks 5 and 6 are recorded next to the second closed session as shown in FIG. 8, the microcomputer 36 reads out position information of the second lead-in area 'LIA2' from the first lead-in area 'LIA1', and knows next recording position, that is, the position of track 5 from the second lead-in area 'LIA2'. Since the program area containing the tracks 5 and 6 is not closed into a session (S34), the microcomputer 36 examines the PMA information to know how many tracks are
10 first lead-in area 'LIA1', and knows next recording position, that is, the position of track 5 from the second lead-in area 'LIA2'. Since the program area containing the tracks 5 and 6 is not closed into a session (S34), the microcomputer 36 examines the PMA information to know how many tracks are
15 recorded in the disk 1 and locates final recorded track based on the PMA information (S35).

However, if the PMA has wrong information of position and size about track 6 or has not since a servo control malfunctioned due to an external shock or a data buffer was underruned during
20 recording the track 6, the microcomputer 36 considers the track 5, which was recorded normally, as the last one based on the PMA information although the track 6 has been formed in the disk 1 owing to partial recording.

To prepare for such an abnormal case, the microcomputer
25 36 does not write new data next to the track 5, instead, the microcomputer 36 controls the pickup 32 to reproduce from the ending point of the track 5 to a certain extent. Then, the microcomputer 36 checks whether the signals outputted from the R/F unit 33 are EFM-formatted binary signals (S37). If the
30 output is binary signal of which state is toggled, the area following the track 5 is not blank, if not, it is blank.

If the area following the track 5 is blank, the microcomputer 36 returns the pickup 32 to the position which

6 are recorded next to the second closed session, and the position and size information about tracks 1 to 6 are written in the PMA, however the size of the last track 6 written in the PMA is not identical to the size of actually-recorded track 6 because of momentary buffer-underrun, etc. during recording the track 6.

A data writing method for the case of FIG. 9 is conducted as follows.

As explained above for the flow of FIG. 7, when a user requests new data to be recorded in an inserted disk 1, the microcomputer 36 sets its mode to recording mode, conducts the OPC, and sets an optimal writing power determined through the OPC into the writing driver 32. After the OPC, the microcomputer 36 reads position and size information, which is recorded in the PMA, about recorded tracks, and searches for the first lead-in area, the second, and the third, in turn based on the PMA information and chained information between lead-in areas. That is, the microcomputer 36 reads out position information of the second lead-in area 'LIA2' from the first lead-in area 'LIA1', and knows next recording position, i.e., the position of track 5 from the second lead-in area 'LIA2'. Since the program area containing the tracks 5 and 6 is not closed into a session, the microcomputer 36 examines the PMA information to know how many tracks are recorded and locates final recorded track, which will be track 6, based on the PMA information.

To resolve the abnormal case in which the PMA and actually-recorded track 6 are not same in size due to momentary buffer underrun etc., the microcomputer 36 does not write new data after the final recording position calculated based on the PMA information on the track 6, instead, it controls the pickup 32 to reproduce from the final position to a certain extent. Then, the microcomputer 36 checks whether the signal outputted from the R/F unit 33 is EFM-formatted binary signal. If the

output signal is binary, the area following the final position is not blank, if not, it is blank.

In the case that the area is not blank, when the reproduced signal makes transition from binary to constant, the
5 microcomputer 36 recognizes the transition point as a substantial last point of the track 6, and closes an area from the starting point of the track 5 to the recognized last point in a session as writing necessary information in lead-in 'LIA3' and lead-out area 'LOA3' after securing the lead-out area
10 'LOA3'.

After that, the microcomputer 36 controls new data to be written in a program area as track 7 after the just-closed session, so that the new data is never overlapped partially with the track 6 of which recorded size is not identical to the size
15 information of the PMA.

Another example of recorded data is shown in FIG. 10 in which tracks 1 and 2 belong to the first closed session, tracks 3 and 4 to the second closed session, and tracks 5 and 6 to the third session, and the position and size information about
20 tracks 1 to 6 are normally written in the PMA, however the third lead-in area has wrong information on the next recording position or does not have it because of a mechanical shock or a buffer-underrun, etc. occurred during closing the third session. A data writing method for the case of FIG. 10 is
25 conducted as follows.

As explained above for the procedure of FIG. 7, when a user requests new data to be recorded in an inserted disk 1, the microcomputer 36 sets its mode to recording mode, conducts the OPC, and sets an optimal writing power determined through
30 the OPC into the writing driver 32. After the OPC, the microcomputer 36 reads out position information of the second lead-in area 'LIA2' from the first lead-in area 'LIA1', reads out position information of the third lead-in area 'LIA3' from

the second lead-in area 'LIA2', and tries to read out the next recording position for new data from the third lead-in area 'LIA3'.

However, the reading of the third lead-in area 'LIA3' fails due to abnormal recorded state which was made from a servo or writing fail caused by a mechanical shock, etc. Therefore, the microcomputer 36 controls the pickup 32 to reproduce from the starting point of the third program area next to the lead-in area 'LIA3', and checks whether the signal outputted from the R/F unit 33 is changed from EFM-formatted binary signal to constant signal. If the output signal is changed from binary to constant and the constant level maintains more than a pause period, the microcomputer 36 considers the changed position as an ending position of the track 6, i.e., the last track of the uncompleted session 3.

After detecting the actual recordable position, the microcomputer 36 secures the fourth lead-in area 'LIA4', and then controls new data to be written in a program area as track 7 (S38) after the secured lead-in area 'LIA4',

With the above-explained writing operation, new data is normally written in a blank area following the uncompleted session 3 even though the lead-in area of the uncompleted session 3 has abnormal data or has not position information on the next recording position.

In the above case that a lead-in area is invalid, a linking session may be created as shown in FIG. 11. The linking session contains one track of null data, a lead-in area whose information points the next recording position, that is, a lead-in area of new session 5 for new data, and a lead-out area.

Therefore, lead-in areas containing tracks which are recorded and closed in sessions normally are linked after the null session.

In the explained cases that the size of a track written

in the PMA is not identical to the size of an actually-recorded track and that a lead-in area has wrong position information on the next recording position or has not, the microcomputer 36 may inform a user of the abnormal condition by outputting 5 an advisory message, and correct wrong information, if it is rewritable and correctable, according to the request of a user.

The method and apparatus for determining a recordable position of a writable disk according to the present invention, enables new data not to be overwritten onto previous data of 10 which recording was interrupted by a servo or writing fail caused from a mechanical shock, thereby preventing new data to be recorded as well as previous data from being damaged or lost.

The invention may be embodied in other specific forms without departing from the spirit or essential characteristics 15 thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are 20 therefore intended to be embraced therein.

What is claimed is:

1. A method of searching for a recordable position of a writable disk, comprising the steps of:

(a) reading data recording information of the writable 25 disk;

(b) examining whether an area after a recordable position indicated by the read data recording information has recorded data or not; and

(c) changing the recordable position to other position 30 for new input data based on the examination result.

2. The method set forth in claim 1, wherein the data recording information consists of track position information of a program memory area and lead-in area information.

3. The method set forth in claim 1, wherein said step (b) scans a predetermined amount of physical tracks as checking whether a reproduced signal is changed from binary-toggling state to a constant level.

5 4. The method set forth in claim 3, wherein the predetermined amount of physical tracks is longer than a pause section specified to be gapped between two tracks.

5. The method set forth in claim 1, wherein said step (c) closes recorded data located ahead of the examined actual final
10 position of recorded data in a session, and determines a new recordable position apart from the closed session.

6. The method set forth in claim 5, wherein said step (c) determines the new recordable position separated as much as a lead-in area from the closed session.

15 7. The method set forth in claim 1, wherein said step (c) determines a new recordable position separated from the examined actual final position of recorded data by a predetermined amount of physical tracks.

8. The method set forth in claim 7, wherein the
20 predetermined amount of physical tracks is longer than a pause section specified to be gapped between two tracks.

9. A method of searching for a recordable position of a writable disk, comprising the steps of:

(a) checking whether a previous recording has been done
25 normally;

(b) examining a recording area affected by a writing beam during the previous recording based on the checked result; and

(c) determining a recordable position for new input data based on the examination result.

30 10. The method set forth in claim 9, wherein said step (a) checks whether the previous recording of either a program memory area containing information of data tracks or a lead-in area containing information of a session has been done normally.

11. The method set forth in claim 9, wherein said step (c) closes recorded data of which recording has been done abnormally in a session, and determines a new recordable position apart from the closed session.

12. The method set forth in claim 11, wherein said step (c) determines the new recordable position separated as much as a lead-in area from the closed session.

13. The method set forth in claim 9, wherein said step (c) determines a new recordable position separated as much as a predetermined amount of physical tracks from a final position of recorded data of which recording has been done abnormally.

14. The method set forth in claim 13, wherein the predetermined amount of physical tracks is longer than a pause section specified to be gapped between two tracks.

15. An apparatus for recording and reproducing to and from a writable disk, comprising:

a pickup of writing input data and reading the written data to/from the writable disk;

a moving means of moving the pickup across the writable disk; and

a controller of controlling the moving means to move the pickup to a recordable position indicated by data recording information which was updated after previous data recording, checking whether or not data has been recorded after the indicated recordable position through examining the state of a recording surface state of the writable disk, and changing the recordable position for the new data to other position based on the checked result.

16. The apparatus set forth in claim 15, wherein the controller controls the pickup to write data necessary to close recorded data into a session if data has been recorded after the indicated recordable position.


17. The apparatus set forth in claim 15, wherein the

controller determines whether data has been recorded after the indicated recordable position based on whether the recording surface state is binary-toggling or constant.

ABSTRACT OF DISCLOSURE


The present invention relates to method and apparatus for recording new data in a writable disk such as an once-writable disk CD-R and a rewritable disk CD-RW after previous recording to the disk is interrupted abnormally. A method of determining a recordable position of a writable disk according to the present invention, reads data recording information of the writable disk, examines whether an area after a recordable position indicated by the read data recording information has recorded data or not, and changes the recordable position to other position for new input data if the area has recorded data since previous recording was done incompletely. Therefore, new data is always written after uncompleted data track without being overlapped with previous data even though the recording information of an uncompleted data track is wrong or unusable. The method and apparatus for determining a recordable position of a writable disk according to the present invention, enables new data not to be overwritten onto previous data of which recording was interrupted by a servo or writing fail caused from a mechanical shock, thereby preventing new data to be recorded as well as previous data from being damaged or lost.

FIG. 1




Conventional Art

FIG. 2




Conventional Art

FIG. 3




Conventional Art

FIG. 4



Conventional Art

FIG. 5



Conventional Art

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



BIRCH, STEWART, KOLASCH & BIRCH, LLP

P.O. Box 747 • Falls Church, Virginia 22040-0747
Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE:
YOU MUST
COMPLETE THE
FOLLOWING

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT AND DESIGN APPLICATIONS

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated next to my name, that I verily believe that I am the original, first and sole inventor (if only one inventor is named below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Insert Title

METHOD AND APPARATUS FOR DETERMINING A RECORDABLE POSITION OF A WRITABLE DISK

Fill in Appropriate
Information -
For Use Without
Specification
Attached

the specification of which is attached hereto. If not attached herein,

the specification was filed on _____ as
United States Application Number _____;
and amended on _____ (if applicable) and/or
the specification was filed on _____ as PCT
International Application Number _____; and was
amended under PCT Article 19 on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representative or assigns more than twelve months (six months for designs) prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows:

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Insert Priority
Information
(If Appropriate)

Prior Foreign Application(s)

Priority Claimed

(Number)	(Country)	(Month/Day/Year Filed)	Yes	No
99-39944	Korea	09/16/99	<input checked="" type="checkbox"/>	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

Insert Provisional
Application(s)
(If any)

(Application Number)	(Filing Date)
_____	_____
_____	_____

All Foreign Applications, if any, for any Patent or Inventor's Certificate Filed More than 12 Months (6 Months for Designs) Prior to the Filing Date of This Application:

Insert Requested
Information:
(If appropriate)

Country	Application Number	Date of Filing (Month/Day/Year)
_____	_____	_____
_____	_____	_____

I hereby claim the benefit under Title 35, United States Code, §120 of any United States and/or PCT application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States and/or PCT application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to the patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Insert Prior U.S.
Application(s)
(If any)

(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)
_____	_____	_____
_____	_____	_____

Attorney Docket No.

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary.

Raymond C. Stewart	(Reg. No. 21,066)	Terrell C. Birch	(Reg. No. 19,382)
Joseph A. Kolasch	(Reg. No. 22,463)	James M. Slattery	(Reg. No. 28,380)
Bernard L. Sweeney	(Reg. No. 24,448)	Michael K. Mutter	(Reg. No. 29,680)
Charles Corenstein	(Reg. No. 29,271)	Gerald M. Murphy, Jr.	(Reg. No. 28,977)
Leonard R. Svensson	(Reg. No. 30,330)	Terry I. Clark	(Reg. No. 32,644)
Andrew D. Meikle	(Reg. No. 32,868)	Marc S. Weiner	(Reg. No. 32,181)
Joe McKinney Muncy	(Reg. No. 32,334)	Donald J. Daley	(Reg. No. 34,313)
John W. Bailey	(Reg. No. 32,881)	John A. Castellano	(Reg. No. 35,094)
Gary D. Yacura	(Reg. No. 35,416)		

Send Correspondence to

BIRCH, STEWART, KOLASCH & BIRCH, LLP

or Customer No. 2292

P.O. Box 747 • Falls Church, Virginia 22040-0747

Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE:
YOU MUST
COMPLETE
THE
FOLLOWING:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of First or Sole Inventor Insert Name of Inventor Insert Date This Document is Signed		Full Name of First or Sole Inventor Insert Name of Inventor Insert Date This Document is Signed	
GIVEN NAME/FAMILY NAME <i>Jim-Tae Roh</i>		INVENTOR'S SIGNATURE <i>[Signature]</i>	
DATE*		<i>09/07/00</i>	
Residence (City, State & Country) <i>Kyunggi-do, Korea</i>		CITIZENSHIP <i>Republic of Korea</i>	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) <i>606-304, Hyundai Apt., Pyungchon-dong, Dongan-gu, Anyang, Kyunggi-do, 431-070, Republic of Korea</i>			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	
DATE*			
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	
DATE*			
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	
DATE*			
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME/FAMILY NAME		INVENTOR'S SIGNATURE	
DATE*			
Residence (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			

*DATE OF SIGNATURE